

SiwoPUD®-1512X2

Characteristics:	It is an aqueous anionic dispersion based on polyester.	
Supplied as:	35% in water	
Physical characteristics:	Appearance	Translucence
	Non-volatile constituent	35±1 %
	PH value	7.0 – 9.0
	Viscosity	≤200 mPa·s
	NMP, NEP, DMAC, etc.	Free
	Elongation	1400-1500%
	Tensile strength	26.5 Mpa
	100%Modulus	1.6 Mpa
	Yellowing resistance	non- yellowing
Storage:	The dispersion should be stored in a frost-free place in tightly sealed containers. It contains no preservative.	
Application:	Its film is soft, elastic, and has excellent adhesion on the substrate such as PVC, PET, OPP, BOPP, umbrella fabric and nylon etc. It is suitable for the substrate that is difficult to adhere to. PUD- 1512X2 is an enhanced version of PUD-1512LF.	

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication. Nothing herein is to be construed as a warranty, express or otherwise. In all cases, it is the responsibility of the users to determine the applicability of such information or suitability of any products for their own purposes. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such is free of patent infringement and are not recommendations to infringe on any patent.