

## SiwoPUD®- 201

**Characteristics:** Aqueous, aliphatic polyurethane dispersion based on polycarbonate and polyester.

**Supplied as:** 35% in water

Physical characteristics: Appearance Translucence

 $\begin{array}{lll} \mbox{Non-volatile constituent} & 35\pm 1~\% \\ \mbox{PH value} & 7.0 - 9.5 \\ \mbox{Viscosity} & \leqslant 200 \mbox{mPa} \cdot \mbox{s} \\ \mbox{Mean particle size} & \leqslant 100~\mbox{nm} \\ \mbox{Glass transition temperature Tg} & -25~\% \\ \mbox{NMP, NEP, DMAC} & \mbox{Free} \end{array}$ 

Elongation 400-500%
Tensile strength 25.7Mpa
100%Modulus 4.3Mpa
Shear stability good
Dry Fast

Yellowing resistance non- yellowing

Storage: The dispersion should be stored in a frost-free place in tightly sealed containers. It

contains no preservative.

**Application:** Its surface drying is slow. It exhibits excellent adhesion, good water resistance. It

is suitable for fabric coatings and printing inks.

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication. Nothing herein is to be construed as a warranty, express or otherwise. In all cases, it is the responsibility of the users to determine the applicability of such information or suitability of any products for their own purposes. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such is free of patent infringement and are not recommendations to infringe on any patent.